

Data Sheet

Fujitsu Server PRIMERGY BX924 S4 Dual Socket Server Blade

High-end server blade with maximum scalability for demanding applications

FUJITSU Server PRIMERGY systems provide the most powerful and flexible data center solutions for companies of all sizes, across all industries and for any type of workload. This includes expandable PRIMERGY tower servers for remote and branch offices, versatile rack-mount servers, compact and scalable blade systems, as well as density-optimized scale-out servers. They convince by business proven quality with a wide range of innovations, highest efficiency cutting operational cost and complexity, and provide more agility in daily operations in order to turn IT faster into a business advantage.

FUJITSU Server PRIMERGY BX blade systems are the perfect platform to build a converged infrastructure designed to reduce IT costs, time and efforts. PRIMERGY Blade Servers utilizes a modular architecture and contain in addition to the compute power, all required infrastructure and network components, storage capacity as well as management modules that helps companies to simplify their infrastructure, achieve significant cost reductions and increase flexibility.

PRIMERGY BX924 S4

The Fujitsu Server PRIMERGY BX924 S4 sets new standards in the area of versatility and scalability of dual-socket server blades and thus reinforces its position as a perfect high-end server ideal suited for extensive virtualization and consolidation projects as well as a variety of workloads including demanding high performance computing applications. Meeting a wide range of tomorrow's IT demands while achieving a fast return-on-investment today, this server blade delivers once again a leap forward in performance and modularity even compared to the previous record-breaking generation.

Two CPUs of the Intel® Xeon® processor E5-2600 v2 product family, 24 DIMM slots supporting up to 1,024 GB of DDR3 memory deliver significantly

more performance in same power envelope and enable to run significantly more virtual machines per blade compared to previous generations. The integrated 10 Gbit/s Ethernet Universal Converged Network Adapter provides high networking bandwidth and improves flexibility with the ability to partition the bandwidth, making it ideal to suit the needs of individual applications.

While virtualization allows consolidating of IT resources, it often leads to increased expenses for server administration. Thus the PRIMERGY BX924 S4 delivers state-of-the-art management capabilities with the new integrated Remote Management Controller (iRMC S4) that offers the next generation of remote management functionality. The result is the ability to execute tasks faster, no matter whether the server is located in the server-room next door or in another part of the world.



Features & Benefits

Main Features	Benefits
<p>Boost Application Performance</p> <ul style="list-style-type: none"> Two CPUs with up to 12 cores and 30 MB smart cache, each out of the next generation Intel® Xeon® processor E5-2600 v2 product family with advanced Turbo Boost 2.0 technology, Hyper Threading, two accelerated QPI links and internal Memory Management Unit. Each Intel® QPI link provides the BX924 S4 with a high-speed bandwidth of up to 8 GigaTransfers/second (GT/s) between the individual processors as well as the processors and the up to 24 slots for high-speed (up to 1,866 MHz) memory, which are accessed via 4 channels per CPU. <p>Holistic Server Lifecycle Management</p> <ul style="list-style-type: none"> Save time and conserve valuable IT resources by simplifying remote management with the new, CIM compliant, integrated Remote Management Controller (iRMC S4). The iRMC S4 is based on its successful predecessor iRMC S3 and provides additional functionality such as HDD and RAID monitoring, Video Capturing and virtual media support for multiple CD/DVD, HDD or FDD images or physical drives. Deploy servers quickly, manage virtual or physical server health, and optimize energy consumption with Fujitsu's ServerView Suite, supported by the Intel® Node Manager. <p>Converged Performance</p> <ul style="list-style-type: none"> Integrated 10 Gbit/s Ethernet Universal Converged Network Adapter provides high networking bandwidth and improves flexibility with the ability to partition the bandwidth, making it ideal to suit the needs of individual applications. Two PCIe 3.0 I/O expansion slots (quad channel 1 Gbi/s or dual channel 10 Gbit/s Ethernet, dual channel 8 Gbit/s Fibre Channel, dual channel 10 Gbit/s CNA (FCoE), and dual channel 56 Gbit/s Infiniband) support the highest performing mezzanine option cards now and into the future. Embedded RAID 0/1 controller with support for up to two 2.5-inch SAS/SATA SSD drives. <p>Global Lifecycle Excellence</p> <ul style="list-style-type: none"> Greater value delivered throughout the lifecycle of datacenter systems with the Fujitsu eco-system of business-proven quality, tools, supply-chain flexibility and comprehensive service offerings. 	<ul style="list-style-type: none"> Scalable performance meets the highest requirements for consolidation scenarios with many applications as well as single instance applications, such as database management. Mainly extensive virtualization scenarios on the one hand and demanding high performance computing applications on the other hand are a main domain for this dual socket server blade. Considerably more performance in same power envelope compared to the previous generation enables to run significantly more virtual machines. Improved security with Intel® Secure Key & Intel® OS Guard for additional HW embedded security. Standards conform management via the integrated Remote Management Controller (iRMC S4) enables access to each server and extensive control, even at remote locations. Simplified and comprehensive power management with different selectable power modes results in significant cost savings. ServerView Remote Management enables fully remote control and analysis of Fujitsu PRIMERGY servers irrespective of their system status and location. In the event of a failure administrators or service providers can access the server in order to run failure diagnostics and maintenance tasks on a remote basis and in a highly efficient manner. Common infrastructure for network and storage reduces investment costs (fewer adapters, ports, Connection Blades and switches) as well as operational expenses for IT administration. The high I/O capacity of the server blade allows optimal use of multiple I/O protocols, ensuring smooth operations for demanding applications as well as a balanced operation of virtualized and physical servers in business-critical environments. Fujitsu's broad portfolio of services and tools provide the added benefit of reducing costs throughout the lifecycle, shortening project times and increasing the availability of applications and services.

Technical details

PRIMERGY BX924 S4

Mainboard

Mainboard type	D3143
Chipset	Intel® C600
Processor quantity and type	1 - 2 x Intel® Xeon® processor E5-2600 v2 product family

Processor

Intel® Xeon® processor E5-2603v2 (4C/4T, 1.80 GHz, TLC: 10 MB, Turbo: No, 6.4 GT/s, Mem bus: 1,333 MHz, 80 W)
Intel® Xeon® processor E5-2609v2 (4C/4T, 2.50 GHz, TLC: 10 MB, Turbo: No, 6.4 GT/s, Mem bus: 1,333 MHz, 80 W)
Intel® Xeon® processor E5-2620v2 (6C/12T, 2.10 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s, Mem bus: 1,600 MHz, 80 W)
Intel® Xeon® processor E5-2630Lv2 (6C/12T, 2.40 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s, Mem bus: 1,600 MHz, 60 W)
Intel® Xeon® processor E5-2630v2 (6C/12T, 2.60 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s, Mem bus: 1,600 MHz, 80 W)
Intel® Xeon® processor E5-2637v2 (4C/8T, 3.50 GHz, TLC: 15 MB, Turbo: Yes, 8.0 GT/s, Mem bus: 1,866 MHz, 130 W)
Intel® Xeon® processor E5-2640v2 (8C/16T, 2.00 GHz, TLC: 20 MB, Turbo: Yes, 7.2 GT/s, Mem bus: 1,600 MHz, 95 W)
Intel® Xeon® processor E5-2643v2 (6C/12T, 3.50 GHz, TLC: 25 MB, Turbo: Yes, 8.0 GT/s, Mem bus: 1,866 MHz, 130 W)
Intel® Xeon® processor E5-2650Lv2 (10C/20T, 1.70 GHz, TLC: 25 MB, Turbo: Yes, 8.0 GT/s, Mem bus: 1,600 MHz, 70 W)
Intel® Xeon® processor E5-2650v2 (8C/16T, 2.60 GHz, TLC: 20 MB, Turbo: Yes, 8.0 GT/s, Mem bus: 1,866 MHz, 95 W)
Intel® Xeon® processor E5-2660v2 (10C/20T, 2.20 GHz, TLC: 25 MB, Turbo: Yes, 8.0 GT/s, Mem bus: 1,866 MHz, 95 W)
Intel® Xeon® processor E5-2667v2 (8C/16T, 3.30 GHz, TLC: 25 MB, Turbo: Yes, 8.0 GT/s, Mem bus: 1,866 MHz, 130 W)
Intel® Xeon® processor E5-2670v2 (10C/20T, 2.50 GHz, TLC: 25 MB, Turbo: Yes, 8.0 GT/s, Mem bus: 1,866 MHz, 115 W)
Intel® Xeon® processor E5-2680v2 (10C/20T, 2.80 GHz, TLC: 25 MB, Turbo: Yes, 8.0 GT/s, Mem bus: 1,866 MHz, 115 W)
Intel® Xeon® processor E5-2690v2 (10C/20T, 3.00 GHz, TLC: 25 MB, Turbo: Yes, 8.0 GT/s, Mem bus: 1,866 MHz, 130 W)
Intel® Xeon® processor E5-2695v2 (12C/24T, 2.40 GHz, TLC: 30 MB, Turbo: Yes, 8.0 GT/s, Mem bus: 1,866 MHz, 115 W)
Intel® Xeon® processor E5-2697v2 (12C/24T, 2.70 GHz, TLC: 30 MB, Turbo: Yes, 8.0 GT/s, Mem bus: 1,866 MHz, 130 W)

Memory slots	24 (4 channels per CPU with 3 slots each)
Memory slot type	DIMM (DDR3) registered
Memory capacity (min. - max.)	4 GB - 1536 GB
Memory protection	Advanced ECC Memory Scrubbing SDDC (Chipkill™) Memory Mirroring support Hot-spare memory support

Memory options

4 GB (1 module(s) 4 GB) DDR3 LV, registered, ECC, 1,600 MHz, PC3-12800, DIMM, single rank
8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1,600 MHz, PC3-12800, DIMM, single rank
8 GB (1 module(s) 8 GB) DDR3, registered, ECC, 1,866 MHz, PC3-14900, DIMM, dual rank
16 GB (1 module(s) 16 GB) DDR3 LV, registered, ECC, 1,600 MHz, PC3-12800, DIMM, dual rank
16 GB (1 module(s) 16 GB) DDR3, registered, ECC, 1,866 MHz, PC3-14900, DIMM, dual rank
32 GB (1 module(s) 32 GB) DDR3 LR, registered, ECC, 1,600 MHz, PC3-12800, DIMM, quad rank
32 GB (1 module(s) 32 GB) DDR3 LR, registered, ECC, 1,866 MHz, PC3-14900, DIMM, 4Rx4
64 GB (1 module(s) 64 GB) DDR3 LR, registered, ECC, 1,333 MHz, PC3-10600, DIMM, octo rank

Interfaces

USB 2.0 ports	3 (1x USB at the front side + 2x USB via special cable)
Graphics (15-pin)	1 x VGA at the front via special cable
LAN / Ethernet	2 x 10 Gbit/s or 4 x 1 Gbit/s via Midplane to Ethernet Connection Blade
Management LAN (RJ45)	Management LAN traffic can be switched to shared onboard LAN port

Onboard or integrated Controller

RAID controller	RAID 0/1 for internal drives
SATA Controller	Intel® C600

Onboard or integrated Controller

LAN Controller	Emulex BladeEngine® 3 (BE3). 2 x 10Gbit/s, 2 or 4 x 1Gbit/s Ethernet depending on installed Connection Blade. in 10Gbit/s mode CNA functionality with: - up to 4 physical function per port - optional one storage function (FCoE or iSCSI) with full offload PXE-Boot via LAN from PXE server in all modes FCoE and iSCSI boot in CNA mode PCI-SIG SR-IOV compliant with up to 128 VFs (depending on OS support) Support for VMware NetQueue and Microsoft VMQ optimizes performance for virtualized servers
Remote management controller	Integrated Remote Management Controller (iRMC S4, 256 MB attached memory incl. graphics controller) IPMI 2.0 compatible
Trusted Platform Module (TPM)	Infineon / 1.2 (option)

Slots

PCI-Express 3.0 x8	2 x BX900 Mezzanine card
---------------------------	--------------------------

Drive bays

Storage drive bays	2 x 2.5-inch non hot-plug SATA SSD
---------------------------	------------------------------------

Operating panel

Operating buttons	On/off switch ID button
Status LEDs	Power (amber / green) System status (orange) LAN connection (green) Identification (blue) CSS (yellow)

BIOS

BIOS features	BIOS settings save and restore Local and remote update via ServerView Update Manager Remote PXE boot support SMBIOS V2.6 Online update tools for main Windows and Linux versions ROM based setup utility Local BIOS update from USB device
----------------------	--

Eco System

BX900: Supported with MMB-FW >=5.20
BX400: Supported with MMB-FW >=6.62

Operating Systems and Virtualization Software

Certified or supported operating systems and virtualization software	Microsoft® Hyper-V Server 2012 R2
	Microsoft® Windows Server® 2012 R2 Datacenter
	Microsoft® Windows Server® 2012 R2 Standard
	Microsoft® Windows Storage Server 2012 R2 Standard
	Microsoft® Hyper-V Server 2012
	Microsoft® Windows Server® 2012 Datacenter
	Microsoft® Windows Server® 2012 Standard
	Microsoft® Windows Storage Server 2012 Standard
	Microsoft® Hyper-V™ Server 2008 R2
	Microsoft® Windows Server® 2008 R2 Datacenter
	Microsoft® Windows Server® 2008 R2 Enterprise
	Microsoft® Windows Server® 2008 R2 Standard
	Microsoft® Windows HPC Server® 2008 R2 Suite
	Microsoft® Windows® Small Business Server 2011 Premium Add-On
	Microsoft® Windows® Small Business Server Standard 2011
	Microsoft® Windows® Server 2008 Datacenter
	Microsoft® Windows® Server 2008 Enterprise
	Microsoft® Windows® Server 2008 Standard
	VMware vSphere™ 6.0
	VMware vSphere™ 5.5
	VMware vSphere™ 5.1 Embedded
	VMware vSphere™ 5.1
	VMware vSphere™ 5.0 Embedded
	VMware vSphere™ 5.0
	SUSE® Linux Enterprise Server 12
	SUSE® Linux Enterprise Server 11
	Red Hat® Enterprise Linux 7
	Red Hat® Enterprise Linux 6
	Red Hat® Enterprise Linux 5
	Red Hat® Enterprise Linux 5 with XEN
	Citrix® XenServer®
	Oracle® Linux 7
	Oracle® Linux 6
Oracle® VM 3	
Operating system release link	http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfb3230473
Operating system notes	Support of other Linux derivatives on demand

Server Management

Standard	ServerView Suite - Deploy SV Installation Manager SV Scripting Toolkit ServerView Suite - Control Operations Manager incl. PDA and ASR & R (Prefailure and Analysis; Automatic Server Recovery and Restart) Agents and CIM Providers System Monitor RAID Manager Capacity Management Power Management Storage Support ServerView Suite - Maintain Remote Management (iRMC in combination with Intel® Node Manager) Update Management (BIOS, Firmware, Windows Drives and SV Agents) Performance Measurement Asset Management Online Diagnostics ServerView Suite - Integrate Integration packs e.g. for Microsoft System Center, VMware vCenter, Nagios, HP SIM and others
Option	ServerView VIOM - Virtual IO Manager
Server Management notes	Regarding dependencies for ServerView Suite software products see dedicated product data sheets.
Dimensions / Weight	
Dimensions (W x D x H)	45 x 500 x 210 mm
Weight	7 kg
Weight notes	Actual weight may vary depending on configuration
Environmental	
Temperature note	In accordance with the corresponding PRIMERGY BX900 System Unit
Operating environment	FTS 04230 – Guideline for Data Center (installation specification)
Operating environment link	http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe
Power supply configuration	
Active power (max. configuration)	500 W
Heat emission	1800.0 kJ/h (1706.1 BTU/h)
Compliance	
Global	CB RoHS (Substance limitations in accordance with global RoHS regulations) WEEE (Waste electrical and electronic equipment)
Germany	GS
Europe	CE Class A *
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates
Compliance notes	In combination with corresponding PRIMERGY BX system unit There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

Components

Hard disk drives

HDD SATA, 1 TB, 5,400 rpm, non hot plug, 2.5-inch, economic

Solid-State-Drive	SSD SATA, 6 Gb/s, 800 GB, Mainstream Endurance, non hot plug, 2.5-inch, enterprise
	SSD SATA, 6 Gb/s, 400 GB, Mainstream Endurance, non hot plug, 2.5-inch, enterprise
	SSD SATA, 6 Gb/s, 200 GB, Mainstream Endurance, non hot plug, 2.5-inch, enterprise
	SSD SATA, 6 Gb/s, 100 GB, Mainstream Endurance, non hot plug, 2.5-inch, enterprise
	SSD SAS, 12 Gb/s, 800 GB, Mainstream Endurance, non hot plug, 2.5-inch, enterprise
	SSD SAS, 12 Gb/s, 400 GB, Mainstream Endurance, non hot plug, 2.5-inch, enterprise
	SSD SAS, 12 Gb/s, 200 GB, Mainstream Endurance, non hot plug, 2.5-inch, enterprise
Mezzanine Cards	Ethernet Mezzanine Card 4 x 1 Gbit/s PCIe x4 Fujitsu
	CNA Mezzanine Card 2 x 10 Gbit/s PCIe 2.0 x8 Emulex
	Ethernet Mezzanine Card 2 x 10 Gbit/s PCIe 2.0 x8 Fujitsu
	Fibre Channel Mezzanine Card 2 x 16 Gbit/s PCIe 3.0 x8 Emulex
	Fibre Channel Mezzanine Card 2 x 8 Gbit/s PCIe 2.0 x8 Emulex
	InfiniBand Mezzanine Card 2 x 56 Gbit/s PCIe 3.0 x8 Mellanox
	SAS HBA Mezzanine Card 2 x 6 Gbit/s PCIe 2.0 x8 Fujitsu
	SAS RAID Mezzanine Card 2 x 6 Gbit/s PCIe 2.0 x8 Fujitsu
LAN controller notes	The dual-channel 10 Gbit/s onboard CNA provides either 2x 10 Gbit/s ports, or 4x 1 Gbit/s ports.
Warranty	
Warranty period	3 years
Service level	Onsite warranty
Warranty Terms & Conditions	www.fujitsu.com/support
Product Support Services - the perfect extension	
Support Pack Options	Globally available in major business areas: 9x5, Next Business Day Onsite Response Time 9x5, 4h Onsite Response Time 24x7, 4h Onsite Response Time
Recommended Service	24x7, Onsite Response Time: 4h - For locations outside of EMEA please contact your local Fujitsu partner.
Spare Parts availability	5 years
Service Lifecycle	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/products/product-support-services/

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu PRIMERGY BX924 S4, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu PRIMERGY BX924 S4, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://www.fujitsu.com/>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact
FUJITSU LIMITED

Website: www.fujitsu.com
2015-05-05 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright © Fujitsu Technology Solutions