

Data Sheet

FUJITSU Workstation CELSIUS M740

Bring Your Ideas To Life

The CELSIUS M740 desktop workstation has been optimized to combat today's professional and technical challenges. The CELSIUS M740power is certified for Medical EMC standards IEC60601-1-2 to perform in healthcare environments. To round things off, a near-silent noise emission of 20 dB(A) allows you to work comfortably in the most quiet of working environments.

Performance you can count on

Spectrum of performance due to a wide range of professional grade features

- Next generation Intel® Xeon® processors, high performing graphics subsystems, quad-channel memory technology and high-speed hard disk drives

"IT made in Germany"

From design to production – an "IT made in Germany" quality in which you can trust

- Optimized thermal management and near-silent noise emission of 20 dB(A)

Stringent quality control

System stability through-out the complete lifecycle

- High product standards thanks to top-quality components and comprehensive testing in certified in-house laboratories for 24/7 operation

Certification of workstation applications

Stability, compatibility and performance for the main workstation applications

- Comprehensive support for ISV applications and ease of integration into existing IT networks

Expandability

Excellent expandability for future demands

- Increased memory capacities of up to 256 GB DDR4 memory



Components

Processor

Intel® Xeon® processor E5-2699v3 (18 cores, 2.30 GHz, 45 MB)
 Intel® Xeon® processor E5-2697v3 (14 cores, 2.60 GHz, 35 MB)
 Intel® Xeon® processor E5-2690v3 (12 cores, 2.60 GHz, 30 MB)
 Intel® Xeon® processor E5-2687Wv3 (10 Cores, 3.10 GHz, 25 MB)
 Intel® Xeon® processor E5-2680v3 (12 cores, 2.50 GHz, 30 MB)
 Intel® Xeon® processor E5-2670v3 (12 cores, 2.30 GHz, 30 MB)
 Intel® Xeon® processor E5-2667v3 (8 Cores, 3.20 GHz, 20 MB)
 Intel® Xeon® processor E5-2660v3 (10 Cores, 2.60 GHz, 25 MB)
 Intel® Xeon® processor E5-2650v3 (10 Cores, 2.30 GHz, 25 MB)
 Intel® Xeon® processor E5-2643v3 (6 Cores, 3.40 GHz, 20 MB)
 Intel® Xeon® processor E5-2640v3 (8 Cores, 2.60 GHz, 20 MB)
 Intel® Xeon® processor E5-2637v3 (4 Cores, 3.50 GHz, 15 MB)
 Intel® Xeon® processor E5-2630v3 (8 Cores, 2.40 GHz, 20 MB)
 Intel® Xeon® processor E5-2623v3 (4 Cores, 3.00 GHz, 10 MB)
 Intel® Xeon® processor E5-2620v3 (6 Cores, 2.40 GHz, 15 MB)
 Intel® Xeon® processor E5-2609v3 (6 Cores, 1.90 GHz, 15 MB)
 Intel® Xeon® processor E5-2603v3 (6 Cores, 1.60 GHz, 15 MB)
 Intel® Xeon® processor E5-1680v3 (8 Cores, 3.20 GHz, 20 MB)
 Intel® Xeon® processor E5-1660v3 (8 Cores, 3.00 GHz, 20 MB)
 Intel® Xeon® processor E5-1650v3 (6 Cores, 3.50 GHz, 15 MB)
 Intel® Xeon® processor E5-1630v3 (4 Cores, 3.70 GHz, 10 MB)
 Intel® Xeon® processor E5-1620v3 (4 Cores, 3.50 GHz, 10 MB)
 Intel® Xeon® processor E5-1607v3 (4 Cores, 3.10 GHz, 10 MB)
 Intel® Xeon® processor E5-1603v3 (4 Cores, 2.80 GHz, 10 MB)

Operating systems

| | | |
|-----------------------------|--|--|
| Operating system | Windows 10 Pro Windows 8.1 Pro Windows 7 Professional 64-bit | Windows 10 Pro Windows 8.1 Pro Windows 7 Professional 64-bit |
| Operating system compatible | Windows 8.1 Windows® Server 2012 Linux | Windows 8.1 Windows® Server 2012 Linux |
| Operating system notes | Certified for Red Hat® Enterprise Linux Certified for SUSE Enterprise Desktop Certified for SUSE Enterprise Server | Certified for Red Hat® Enterprise Linux Certified for SUSE Enterprise Desktop Certified for SUSE Enterprise Server |

Memory modules

4 GB (1 module(s) 4 GB) DDR4, registered, ECC, 2,133 MHz, PC4-2133
 8 GB (1 module(s) 8 GB) DDR4, registered, ECC, 2,133 MHz, PC4-2133
 16 GB (1 module(s) 16 GB) DDR4, registered, ECC, 2,133 MHz, PC4-2133
 32 GB (1 module(s) 32 GB) DDR4, registered, ECC, 2,133 MHz, PC4-2133

Graphics

| |
|--|
| Ultra-high-end 3D: NVIDIA® Quadro® M6000, 12 GB, 3,072 cores, PCIe x16, 1x Dual Link DVI-I, 4 x DisplayPort, stereo, SLI |
| Ultra-high-end 3D: AMD FirePro™ W9100, 16 GB, 2816 stream processors, PCIe x16, 6x miniDP, 6x miniDP/DP Adapter |
| Ultra-high-end 3D: NVIDIA® Quadro® M5000, 8 GB, 2304 cores, PCIe x16, 1x Dual Link DVI-I, 4 x DisplayPort |
| Ultra-high-end 3D: NVIDIA® Quadro® K5200, 8 GB, 2304 cores, PCIe x16, 1x Dual Link DVI-I, DVI-D, 2x DisplayPort |
| High-end 3D: AMD FirePro™ W7100, 8 GB, PCIe x16, 4 x DisplayPort |
| High-end 3D: NVIDIA® Quadro® M4000, 8 GB, 1344 cores, PCIe x16, 4 x DisplayPort |
| High-end 3D: NVIDIA® Quadro® K4200, 4 GB, 1344 cores, PCIe x16, 1x Dual Link DVI-I, 2x DisplayPort |
| Midrange 3D: NVIDIA® Quadro® K2200, 4 GB, 640 cores, PCIe x16, 1x Dual Link DVI-I, 2x DisplayPort |
| Midrange 3D: AMD FirePro™ W5100, 4 GB, PCIe x16, 4 x DisplayPort |
| Entry 3D: NVIDIA® Quadro® K1200, 4 GB, 384 cores, PCIe x16, 4x miniDP, 4x miniDP/DP Adapter |
| Entry 3D: AMD FirePro™ W4100, 2 GB, 512 stream processors, PCIe x16, 4x miniDP, 4x miniDP/DP Adapter |
| Entry 3D: NVIDIA® Quadro® K620, 2 GB, 384 cores, PCIe x16, 1x Dual Link DVI-I, 1x DisplayPort |
| Entry 3D: AMD FirePro™ W2100, 2 GB, 320 stream processors, PCIe x16, 2x DisplayPort |
| Entry 3D: NVIDIA® Quadro® K420, 1 GB, 192 cores, PCIe x16, 1x Dual Link DVI-I, 1x DisplayPort |
| Professional 2D: NVIDIA® NVS™ 510, 2 GB, 16 cores, PCIe 2.0 x16, 4x miniDP, 4x miniDP/DP Adapter |
| Professional 2D: NVIDIA® NVS™ 315, 1 GB, 48 cores, PCIe 2.0 x16, 1x LFH59 (max. 2x DP or 2x DVI-I) |
| Professional 2D: NVIDIA® NVS™ 315 fanless, 1 GB, 48 cores, PCIe 2.0 x16, 1x LFH59 (max. 2x DP or 2x DVI-I) |
| GPU computing card: NVIDIA® GRID™ K1 16GB A, 16 GB, 768 cores, PCIe x16 |
| GPU computing card: NVIDIA® GRID™ K2 8GB A, 8 GB, 3,072 cores, PCIe x16 |
| Remote Graphics: CELSIUS RemoteAccess Dual Card, PCIe x1, 2x miniDP, PColP |
| Remote Graphics: CELSIUS RemoteAccess Quad Card, PCIe x1, 4x miniDP, PColP |

Personal Supercomputing

| |
|---|
| Coprocessor: NVIDIA® Tesla® K40, 12 GB, 2,496 cores, PCIe x16 |
| Coprocessor: Intel® Xeon Phi™ Coprocessor 3120A, PCIe x16 |
| Coprocessor: Intel® Xeon Phi™ Coprocessor 5110P, PCIe x16 |

| | |
|-----------------------------|---|
| Hard disk drives (internal) | SSD PCIe 2x512 GB Highend card |
| | SSD PCIe 1x512 GB Highend card |
| | SSD PCIe 2x256 GB Highend card |
| | SSD PCIe 1x256 GB Highend card |
| | SSD SATA III, 400 GB High Endurance, 2.5-inch |
| | SSD SATA III, 200 GB High Endurance, 2.5-inch |
| | SSD SATA III, 1024 GB Mainstream, 2.5-inch |
| | SSD SATA III Premium, 512 GB, 2.5-inch |
| | SSD SATA III Premium, 256 GB, 2.5-inch |
| | SSD SATA III Premium, 128 GB, 2.5-inch |
| | SSD SATA III, 256 GB, 2.5-inch |
| | SSD SATA III, 128 GB, 2.5-inch |
| | SSHD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch |
| | HDD SAS, 15,000 rpm, 600 GB, 2.5-inch |
| | HDD SAS, 15,000 rpm, 300 GB, 2.5-inch |
| | HDD SAS, 10,000 rpm, 1200 GB, 2.5-inch |
| | HDD SAS, 10,000 rpm, 900 GB, 2.5-inch |
| | HDD SAS, 10,000 rpm, 600 GB, 2.5-inch |
| | HDD SAS, 10,000 rpm, 300 GB, 2.5-inch |
| | HDD SATA III, 10,000 rpm, 1,000 GB, 2.5-inch, business critical |
| | HDD SATA III, 10,000 rpm, 500 GB, 2.5-inch, business critical |
| | HDD SATA III, 7,200 rpm, 6,000 GB, 3.5-inch, business critical |
| | HDD SATA III, 7,200 rpm, 4,000 GB, 3.5-inch, business critical |
| | HDD SATA III, 7,200 rpm, 3,000 GB, 3.5-inch, business critical |
| | HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch, business critical |
| | HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch, business critical |
| | HDD SATA III, 7,200 rpm, 2 TB, 2.5-inch, business critical |
| | |
| | HDD SATA III, 7,200 rpm, 1 TB, 2.5-inch, business critical |
| | |
| | HDD SATA III, 7,200 rpm, 1000 GB, 2.5-inch, enhanced availability |
| | HDD SATA III, 7,200 rpm, 500 GB, 2.5-inch, enhanced availability |
| | HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch |
| | HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch |
| | HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch |
| Hard disk notes | <p>*Disk imaging software of the customer must be 4k sector size / advanced format ready</p> <p>One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.</p> <p>24/7 ready (business critical HDDs required)</p> <p>Up to 20 GB of HDD space is reserved for system recovery</p> <p>SSHD (Solid State Hard Disk, Hybrid drive)</p> <p>SED (Self-Encrypting Drive)</p> <p>SSD (Solid State Disk)</p> |
| Drives (optional) | BD Triple Writer SATA slim (tray) |
| | DVD-ROM |
| | DVD Super Multi |
| | DVD Super Multi ultra slim |
| | MultiCard Reader 24in1 USB 2.0 3.5" |
| SCSI / SAS Controller | RAID 5/6 Ctrl. 12 Gbit/s 8 ports int. |
| | RAID 0/1 Ctrl. 12 Gbit/s 8 ports int. |
| | RAID 0/1 Ctrl. 6 Gbit/s 8 ports int. |

**Interface add on cards/components
(optional)**

Gigabit Ethernet PCIe x1, DS
eSATA Interface
Dual serial card PCIe x1
Dual 10 Gigabit Ethernet PCIe x8

| | | |
|-----------|--------------|--------------------|
| Base unit | CELSIUS M740 | CELSIUS M740 power |
|-----------|--------------|--------------------|

Mainboard

| | |
|-------------------------------|--|
| Mainboard type | D3348 |
| Formfactor | ATX |
| Chipset | Intel® C612 |
| Processor socket | Socket R3 |
| Processor quantity maximum | 1 |
| Supported capacity RAM (max.) | 256 GB |
| Memory slots | 8 DIMM (DDR4) ECC |
| LAN | 10/100/1,000 MBit/s Intel® I217LM |
| BIOS version | AMI Aptio V |
| BIOS features | BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) |
| Audio type | On board |
| Audio codec | Realtek ALC671 |
| Audio features | High Definition Audio |

I/O controller on board

| | |
|----------------------|--|
| Serial ATA total | 10 |
| thereof SATA III | 10 |
| Controller functions | Serial ATA III (6 Gbit) AHCI RAID 0/1/5/10 |

Interfaces

| | |
|------------------------|----------------------------------|
| Audio: in (rear) | 1 |
| Audio: out (rear) | 1 |
| Audio: in | 1 |
| Audio: out | 1 |
| Internal speakers | 1 |
| USB 2.0 total | 9 |
| USB 3.0 total | 4 |
| USB front | 4 (2x USB 3.0) |
| USB rear | 6 |
| USB internal | 3, thereof 1 type A |
| Ethernet (RJ-45) | 1 |
| Interface Module notes | Anytime USB charge functionality |

Input device / components

| | |
|--------------------------|---|
| | Optical USB tilt wheel mouse |
| Input devices (optional) | Keyboard Optical USB tilt wheel mouse Optical USB wheel mouse |

Drive bays

| | |
|------------------------|----|
| Drive bays total | 12 |
| 2.5-inch internal bays | 8 |
| 3.5-inch internal bays | 4 |
| 3.5-inch external bays | 2 |

Drive bays

| | |
|-------------------------|--|
| 5.25-inch external bays | 1 |
| Drive bay notes | Up to 8x 2.5-inch HDDs (cold plug) and 1x 2.5-inch SSD or Up to 4x 3.5-inch HDDs (cold plug) and 1x 2.5-inch SSD or Up to 2x 2.5-inch and 2x 3.5-inch HDDs (cold plug) and 1x 2.5-inch SSD |

Slots

| | |
|--------------------------------|---------------------------------------|
| PCI-Express 3.0 x4 (mech. x8) | 1 x (170 mm / 6.69 inch) Full height |
| PCI-Express 3.0 x4 (mech. x16) | 1 x (340 mm / 13.39 inch) Full height |
| PCI-Express 3.0 x16 | 2 x (340 mm / 13.39 inch) Full height |
| PCI-Express 2.0 x4 (mech. x16) | 1 x (340 mm / 13.39 inch) Full height |
| PCI-Express 2.0 x1 (mech. x8) | 2 x (100 mm / 3.94 inch) Full height |

Electrical values

| | | |
|--------------------------------------|---|---|
| Power consumption note | 300 W depending on configuration | 500 W depending on configuration |
| Rated voltage range | 100 V - 240 V | 100 V - 240 V |
| Rated frequency range | 50 Hz - 60 Hz | 50 Hz - 60 Hz |
| Operating voltage range | 90 V - 264 V | 90 V - 264 V |
| Operating line frequency range | 47 Hz - 63 Hz | 47 Hz - 63 Hz |
| Max. output of single power supply | 600 W up to 90% efficiency | 1000 W up to 90% efficiency |
| Power factor correction/active power | active | active |
| Power supply output | 1 graphics power rails (8pin connector / 18.5A@12V) | 2 graphics power rails (8pin connector / 18.5A@12V) |

Noise for standard configuration (HDD, ODD)

| | | |
|--|--|--|
| Related Processors for noise | Intel® Xeon® E5-2687v3 w/ NVIDIA® NVS® 315 | Intel® Xeon® E5-2687v3 w/ NVIDIA® NVS® 315 |
| Standard noise emission | According to ISO 7779:2010, ECMA-74 | According to ISO 7779:2010, ECMA-74 |
| Standard noise notes / description | A-weighted sound power level L _{wad} (in B) / Workplace related A-weighted sound pressure level L _{pAm} (in dB(A)) | A-weighted sound power level L _{wad} (in B) / Workplace related A-weighted sound pressure level L _{pAm} (in dB(A)) |
| Standard noise operation mode: CPU 50% load | 3.7 B / 21 dB(A) Bystander position | 3.7 B / 21 dB(A) Bystander position |
| Standard noise operation mode: CPU 90% load | 3.7 B / 21 dB(A) Bystander position | 3.7 B / 21 dB(A) Bystander position |
| Standard noise operation mode: HDD load | 3.8 B / 22 dB(A) Bystander position | 3.8 B / 22 dB(A) Bystander position |
| Standard noise operation mode: Idle mode | 3.7 B / 21 dB(A) Bystander position | 3.7 B / 21 dB(A) Bystander position |
| Standard noise operation mode: ODD load | 4.5 B / 27 dB(A) Bystander position | 4.5 B / 27 dB(A) Bystander position |
| Standard noise operation mode: Office applications 2.0 | 3.7 B / 21 dB(A) Bystander position | 3.7 B / 21 dB(A) Bystander position |

Dimensions / Weight / Environmental

| | |
|-------------------------------|---|
| Dimensions (W x D x H) | 186 x 481 x 430 mm 7.32 x 18.9 x 16.9 inch |
| Operating position | Vertical / horizontal |
| Weight | approx. 18 kg |
| Weight (lbs) | approx. 39.67 lbs |
| Weight notes | Actual weight may vary depending on configuration |
| Operating ambient temperature | 10 - 35 °C (50 - 95 °F) |
| Operating relative humidity | 5 - 85 % (relative humidity) |

Compliance

| | | |
|------------------------|--|--------------------|
| Product | CELSIUS M740 | CELSIUS M740 Power |
| Model | ETNA_S-D3348 | |
| Germany | GS depending on configuration | |
| Europe | CE | |
| USA/Canada | FCC Class B cCSAus | |
| Global | RoHS (EU & China) Microsoft Operating Systems (HCT / HCL entry / WHQL) WEEE (Waste electrical and electronic equipment) EPEAT® Silver (dedicated regions) ENERGY STAR® 5.0 (dedicated regions) | |
| Taiwan | BSMI | |
| Compliance link | http://globalsp.ts.fujitsu.com/sites/certificates | |

Additional Software

| | |
|---|--|
| Additional software (preinstalled) | Workplace Protect (secure authentication solution) McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version) Microsoft Office (buy license to activate the pre-installed Microsoft Office) |
| Additional software (optional) | Drivers & Utilities DVD (DUDVD) Windows® 8 and Windows® 7 |

Security

| | | |
|---------------------------------|--|--|
| Physical Security | Kensington Lock support Eye for padlock Intrusion switch Integrated cabinet lock (optional) | Kensington Lock support Eye for padlock Intrusion switch Integrated cabinet lock (optional) |
| System and BIOS Security | Write protect option for the Flash EPROM Boot protection for floppy disk / CD drive and write protection for floppy disk drive Control of all USB interfaces Trusted platform module (TPM 1.2) EraseDisk | Write protect option for the Flash EPROM Boot protection for floppy disk / CD drive and write protection for floppy disk drive Control of all USB interfaces Trusted platform module (TPM 1.2) EraseDisk |
| User Security | User and supervisor BIOS password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional) | User and supervisor BIOS password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional) |

Manageability

| | |
|---------------------------------|--|
| Manageability technology | DeskUpdate Driver management iAMT 9.0 (depending on CPU) |
| Manageability software | DeskView Client DeskView Instant BIOS Management DeskView Integration for Symantec Management Platform |
| DeskView components | Inventory Management BIOS Management Driver Management Security Management Alarm Management |
| Supported standards | WMI BootP (made4you) PXE WoL (Wake on LAN) |
| Manageability link | http://www.fujitsu.com/fts/manageability |

Miscellaneous

| | | |
|--------------------------------|---------------------|---------------------|
| | Rack mountable (5U) | Rack mountable (5U) |
| Spare part availability | 5 years | 5 years |

Packaging information

| | | |
|-----------------------------------|--------------------------|---------------------------|
| Packaging dimension (mm) | 397 x 597 x 597 mm | 397 x 597 x 555 mm |
| Packaging dimension (inch) | 15.63 x 23.5 x 23.5 inch | 15.63 x 23.5 x 21.85 inch |
| Max. quantity / pallet | 16 | 16 |

Packaging information

| | |
|-----------------|--------|
| Packaging notes | 597 mm |
|-----------------|--------|

Warranty

| | |
|-----------------|--------------------------------|
| Warranty period | 3 years (depending on country) |
|-----------------|--------------------------------|

| | |
|---------------|---|
| Warranty type | Bring-In / Onsite Service (for countries within region FTS CEMEA&I, for all other countries depending on local regulations, minimum: 3 years material warranty) |
|---------------|---|

| | |
|-----------------------------|---|
| Warranty Terms & Conditions | http://support.ts.fujitsu.com/warranty |
|-----------------------------|---|

Product Support Services - the perfect extension

| | |
|---------------------|--|
| Recommended Service | 9x5, Onsite Response Time: Next Business Day |
|---------------------|--|

| | |
|--------------------------|-----------------------------------|
| Spare Parts availability | 5 years after end of product life |
|--------------------------|-----------------------------------|

| | |
|-----------------|---|
| Service Weblink | http://www.fujitsu.com/fts/services/support |
|-----------------|---|

Recommended Accessories

Display P24W-7 LED

If you're a pixel, color and performance-hungry professional using demanding applications, the FUJITSU P24W-7 LED Display is the perfect choice. The display provides outstanding picture performance thanks to a cutting-edge graphic panel. It also boasts unique and innovative features such as our patent-applied Presence Sensor technology and the Always Available Powered USB Hub.

Order Code:
S26361-K1498-V140

Display P27T-7 UHD

For pixel, color and performance-hungry professionals using demanding applications, look no further than the FUJITSU P27T-7 UHD Display. It provides outstanding picture quality with Ultra High Definition (UHD) resolution, also known as 4k. Picture in Picture (PiP), unrivalled ergonomics, a multitude of UHD supporting interfaces and manageability make this the perfect choice.

Order Code:
S26361-K1564-V140

Blue LED Mouse GL9000

Blue LED Mouse GL9000 comes in a slim design with proven Fujitsu engineering quality. The state-of-the-art blue LED sensor enables ultra precise switchable resolution at 1,000, 1,500 and 2,000 dpi. Blue LED Mouse GL9000 makes your life easier because it's tailor-made for right handed users. It just feels great in your hand.

Order Code:
S26381-K438-L100

SpaceMouse™ Pro

Using the SpaceMouse™ Pro 3D mouse to navigate 3D models or environments is as simple as holding them in your hand. A slight movement of the controller cap delivers easy and precise control. SpaceMouse™ Pro is a companion to the traditional mouse and is operated with the free hand. Your traditional mouse hand is free to select, create and edit.

Order Code:
S26381-K459-L100

Keyboard KBPC PX ECO

Fujitsu's KBPC PX ECO keyboard is the perfect contribution to Green IT. The keyboard is made out of 45% renewable raw material and comes with a PVC free USB cable. In addition, the KBPC PX ECO offers first class comfort and ergonomics. It attracts attention with its impressive modern design and useful extras.

S26381-K341-L1** (**: country specific variation)

More information

Fujitsu OPTIMIZATION Services

In addition to the FUJITSU Workstation CELSIUS M740, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about the FUJITSU Workstation CELSIUS M740, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/CELSIUS

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
© 2015 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions
Website: www.fujitsu.com/fts
2016-01-06 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
© 2015 Fujitsu Technology Solutions GmbH