

Data Sheet

FUJITSU Workstation CELSIUS W520 Long Lifecycle

Long Lifecycle CELSIUS W520

If you need a stable, single-processor desktop workstation for entry-level 3D or CAD applications and the support of a legacy PCI slot, the FUJITSU CELSIUS W520 Long Lifecycle gives you the graphics capabilities, power and stability throughout a minimum lifecycle of 36 months.

Long lifecycle

Continuity and availability for long-term projects

- Minimum lifecycle of 36 months
- Legacy PCI slot

Powerful desktop workstation

Get more done in less time

- The fastest available processors, graphics cards and hard disk drives for entry-level 3D/CAD or DCC applications

Quality

Highest quality and reliability for continuous productivity

- Designed and manufactured in Germany

Leading workstation application certification

Maximum compatibility and performance with customer-preferred applications

- Full support for ISV applications and easy integration into existing IT environments

Easy and rapid change of hard disk drives

Quick upgrades and changes of hard disk drives

- Cold plug access at front



Components

Processor	Intel® Core™ i3-3220 processor (2 Cores / 4 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 2500)
	Intel® Xeon® processor E3-1275v2 (4 Cores / 8 Threads, 3.50 GHz, up to 3.9 GHz, 8 MB, Intel® HD Graphics P4000)
	Intel® Xeon® processor E3-1225v2 (4 Cores / 4 Threads, 3.20 GHz, up to 3.6 GHz, 8 MB, Intel® HD Graphics P4000)
	Intel® vPro™ with all Intel® Xeon® processors
Operating systems	
Operating system	Windows 8.1 Pro
	Windows 7 Professional 64-bit
	Windows 7 Professional 32-bit
Operating system compatible	Windows 10 Pro
	Windows 10
	Windows 8.1
	Windows® XP
	Linux
Operating system notes	Certified for Red Hat® Enterprise Linux
	Certified for SUSE Enterprise Desktop
	Certified for SUSE Enterprise Server
	For some configurations third party drivers are currently not available or configuration restrictions may apply. Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via http://support.ts.fujitsu.com
Memory modules	
	4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1,600 MHz, PC3-12800, DIMM
	4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1,600 MHz, PC3-12800, DIMM
	8 GB (1 module(s) 8 GB) DDR3, unbuffered, ECC, 1,600 MHz, PC3-12800, DIMM
	8 GB (1 module(s) 8 GB) DDR3, unbuffered, non-ECC, 1,600 MHz, PC3-12800, DIMM
Graphics	
	High-end 3D: NVIDIA® Quadro® M4000, 8 GB, 1344 cores, PCIe x16, 4 x DisplayPort
	High-end 3D: NVIDIA® Quadro® K4200, 4 GB, 1344 cores, PCIe x16, 1x Dual Link DVI-I, 2x DisplayPort
	Midrange 3D: NVIDIA® Quadro® K2200, 4 GB, 640 cores, PCIe x16, 1x Dual Link DVI-I, 2x DisplayPort
	Entry 3D: NVIDIA® Quadro® K620, 2 GB, 384 cores, PCIe x16, 1x Dual Link DVI-I, 1x DisplayPort
	Entry 3D: NVIDIA® Quadro® K420, 1 GB, 192 cores, PCIe x16, 1x Dual Link DVI-I, 1x DisplayPort
	Professional 2D: NVIDIA® NVS™ 510, 2 GB, 16 cores, PCIe 2.0 x16, 4x miniDP, 4x miniDP/DP Adapter
	Professional 2D: NVIDIA® NVS™ 315, 1 GB, 48 cores, PCIe 2.0 x16, 1x LFH59 (max. 2x DP or 2x DVI-I)
	Professional 2D: NVIDIA® NVS™ 315 fanless, 1 GB, 48 cores, PCIe 2.0 x16, 1x LFH59 (max. 2x DP or 2x DVI-I)
	Professional 2D: NVIDIA® NVS™ 310, 512 MB, 16 cores, PCIe 2.0 x16, 2x DisplayPort
	Remote Graphics: CELSIUS RemoteAccess Dual Card, PCIe x1, 2x miniDP, PCoIP
	Remote Graphics: CELSIUS RemoteAccess Quad Card, PCIe x1, 4x miniDP, PCoIP

Hard disk drives (internal)	SSD SATA III, 1024 GB Mainstream, 2.5-inch
	SSD SATA III Premium, 512 GB, 2.5-inch
	SSD SATA III Premium, 256 GB, 2.5-inch
	SSD SATA III Premium, 128 GB, 2.5-inch
	SSD SATA III, 256 GB, 2.5-inch
	SSD SATA III, 128 GB, 2.5-inch
	SSD SATA III, 256 GB, 2.5-inch, SED
	SSD SATA III, 128 GB, 2.5-inch, SED
	SSHD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch
	SSHD SATA III, 5,400 rpm, 500 GB, 2.5-inch
	HDD SATA III, 10,000 rpm, 1,000 GB, 2.5-inch, business critical
	HDD SATA III, 10,000 rpm, 500 GB, 2.5-inch, business critical
	HDD SATA III, 7,200 rpm, 6,000 GB, 3.5-inch, business critical
	HDD SATA III, 7,200 rpm, 4,000 GB, 3.5-inch, business critical
	HDD SATA III, 7,200 rpm, 3,000 GB, 3.5-inch, business critical
	HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch, business critical
	HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch, business critical
	HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch, business critical
	HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch
	HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch
	HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch
Hard disk notes	<p>One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.</p> <p>24/7 ready (business critical HDDs required)</p> <p>Up to 20 GB of HDD space is reserved for system recovery</p> <p>SSHD (Solid State Hard Disk, Hybrid drive)</p> <p>SED (Self-Encrypting Drive)</p> <p>SSD (Solid State Disk)</p>
Drives (optional)	BD Triple Writer SATA slim (tray)
	DVD-ROM
	DVD Super Multi
	MultiCard Reader 24in1 USB 2.0 3.5"
Interface add on cards/components (optional)	
	Parallel Interface
	Gigabit Ethernet PCIe x1, DS
	eSATA Interface
	Dual serial card PCIe x1
Base unit	CELSIUS W520power-L
Mainboard	
Mainboard type	D3167
Formfactor	ATX
Chipset	Intel® C216
Processor socket	LGA 1155
Processor quantity maximum	1
Supported capacity RAM (max.)	32 GB
Memory slots	4 DIMM (DDR3) ECC/non-ECC
Memory frequency	1,600 MHz
Memory notes	<p>Dual channel support</p> <p>For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same.</p>
LAN	10/100/1,000 MBit/s Intel® 82579 LM

Mainboard

BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio type	On board
Audio codec	Conexant CX20642
Audio features	Internal speaker supports audio playback, High Definition audio, 5.1 surround sound

I/O controller on board

Serial ATA total	6
thereof SATA III	2
thereof eSATA	2 (optional)
Controller functions	Serial ATA II (3 Gbit) Serial ATA III (6 Gbit) NCQ AHCI RAID 0/1/5/10 (Windows XP not supported) Intel® Smart Response Technology (depending on CPU)
SATA RAID support	0, 1, 10, 5

Interfaces

Audio: in (rear)	2
Audio: out (rear)	1
Audio: in	1
Audio: out	1
Internal speakers	1
USB 2.0 total	10
USB 3.0 total	4
USB front	2x 2.0/ 2x 3.0
USB rear	6x 2.0 / 2x 3.0
USB internal	2
VGA	1 (depends on processor, via DVI to VGA adapter)
DisplayPort	1
DVI	1 (depends on processor)
Serial (RS-232)	1 (9pin, 16 byte FIFO, 16550 compatible)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
Parallel	1, optional (25pin with EPP and ECP)
eSATA	1 (optional)
Interface Module notes	Anytime USB charge functionality

Input device / components

	Optical USB tilt wheel mouse
Input devices (optional)	Optical USB/PS2 tilt wheel mouse Laser Mouse GL9000 Mouse M440 ECO Space Explorer USB KBPC PX ECO Keyboard

Drive bays

Drive bays total	8
3.5-inch internal bays	4
3.5-inch external bays	2
5.25-inch external bays	2
Drive bay notes	Up to 4x 2.5-inch HDDs (cold plug) or Up to 4x 3.5-inch HDDs (cold plug) or Up to 2x 2.5-inch and 2x 3.5-inch HDDs (cold plug)

Slots

PCI-Express 3.0 x16	1 x (312 mm / 12.29 inch) Full height
PCI-Express 2.0 x4 (mech. x16)	1 x (210 mm / 8.27 inch) Full height
PCI-Express x1	3 x (312 mm (2x) / 170 mm (1x) mm / 12.29 inch (2x) / 6.69 inch (1x) inch) Full height
PCI (32-bit / 33 MHz)	2 x (312 mm / 12.29 inch) Full height

Graphics on board

Shared video memory	up to 1,759 MB
TFT resolution (VGA)	1,024 x 768 pixel 1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,600 x 1,200 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel
TFT resolution (DVI)	1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel
TFT resolution (DisplayPort)	1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel 2,560 x 1,440 pixel 2,560 x 1,600 pixel
Graphics features	Dual display support DirectX® 10.1 or DirectX® 11 (depending on CPU) HDCP support Open GL® 3.1 Open CL® 1.1 For multi monitoring mode, graphics card and integrated graphics run in parallel (Microsoft® Windows® 7 or Windows 8)
Graphics notes	Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz

Electrical values

Power efficiency note	power supply efficiency (at 230V; 20% / 50% / 100% load) : 87% / 90% / 87%
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	500 W
Power factor correction/active power	active
Power supply output	1 graphics power rail (6pin connector / 17A@12V)

Noise for standard configuration (HDD, ODD)

Noise Operation mode 4: High load	18 dB(A)
Noise Operation mode 5: Office applications	18 dB(A)
Standard noise emission	2x2 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74
Standard noise notes / description	A-weighted sound power level Lw _{ad} (in B) / Workplace related A-weighted sound pressure level Lp _{Am} (in dB(A)) (depending on configuration)
Standard noise operation mode: HDD load	4.0 B / 24 dB(A) Bystander position

Noise for standard configuration (HDD, ODD)

Standard noise operation mode: Idle mode 3.6 B / 21 dB(A) Bystander position

Standard noise operation mode: ODD load 4.7 B / 30 dB(A) Bystander position

Dimensions / Weight / Environmental

Dimensions (W x D x H) 186 x 481 x 430 mm

Operating position Vertical / horizontal

Weight approx. 16 kg

Weight notes Actual weight may vary depending on configuration

Operating ambient temperature 10 - 35 °C

Operating relative humidity 5 - 85 % (relative humidity)

Compliance

Product CELSIUS W520 POWER

Model ETNA-S-D3167

Germany TÜV GS

Europe CE
Nordic Swan

Global RoHS (Restriction of hazardous substances)
WEEE (Waste electrical and electronic equipment)
Microsoft Operating Systems (HCT / HCL entry / WHQL)
ENERGY STAR® 6.0 (dedicated regions)
EPEAT® Gold (dedicated regions)

Compliance notes Energy Star compliance may vary depending on actual configuration

Compliance link <http://globalsp.ts.fujitsu.com/sites/certificates>

Additional Software

Additional software (preinstalled) Workplace Protect (secure authentication solution)
Adobe® Reader® (pdf reader)
McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version)
Win7: Fujitsu Recovery (hard disk based recovery)
Win8: Microsoft Push Button Recovery (hard disk based recovery)
Microsoft Office (buy license to activate the pre-installed Microsoft Office)

Additional software (optional) Recovery DVD for Windows®
Drivers & Utilities DVD (DUDVD)
CyberLink PowerDVD BD (playback software for Blu-ray Disc™)
CyberLink PowerDVD DVD (playback software for DVD)
Nero Essentials XL

Security

Physical Security Kensington Lock support
Eye for padlock
Seal option
Intrusion switch
Integrated cabinet lock (optional)

System and BIOS Security EraseDisk
Boot sector virus protection
Write protect option for the Flash EPROM
Embedded security (TPM 1.2)
Control of all USB interfaces
External USB ports can be disabled separately
Control of external interfaces

User Security User and supervisor BIOS password
Hard disk password
Access protection via external SmartCard reader (optional)
Access protection via internal SmartCard reader (optional)

Manageability

Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch iAMT 8.0 (depending on CPU) WoL (Wake on LAN)
Manageability software	DeskView 10.x client management including:
DeskView components	On/Offline remote client management Detailed system inventory management and reports BIOS Management Remote power management System notifications Security Remote Control DeskView Helpdesk Integration WoL (Wake on LAN)

Miscellaneous

Keyboard on (Special Fujitsu keyboard required)
 Thermal management
 Extended lifetime
 Rack mountable (5U)

Packaging information

Packaging dimension (mm)	597 x 397 x 555 mm
Packaging dimension (inch)	23.5 x 15.63 x 21.85 inch
Max. quantity / pallet	24
Material - Weight (g) Carton	1858 g
Material - Weight (lbs) Carton	4.1 lbs
Material - Weight (g) EPS / PS	442 g
Material - Weight (lbs) EPS / PS	0.97 lbs
Material - Weight (g) PE	60 g
Material - Weight (lbs) PE	0.13 lbs
Packaging notes	printed user documentation is bleached in chlorine free process

Warranty

Warranty period	3 years (depending on country)
Warranty type	Bring-In / Onsite Service (depending on country)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty

Product Support Services - the perfect extension

Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support

Recommended Accessories

Display P24W-7 LED

If you're a pixel, color and performance-hungry professional using demanding applications, the FUJITSU P24W-7 LED Display is the perfect choice. The display provides outstanding picture performance thanks to a cutting-edge graphic panel. It also boasts unique and innovative features such as our patent-applied Presence Sensor technology and the Always Available Powered USB Hub.

Order Code:
S26361-K1498-V140

Blue LED Mouse GL9000

Blue LED Mouse GL9000 comes in a slim design with proven Fujitsu engineering quality. The state-of-the-art blue LED sensor enables ultra precise switchable resolution at 1,000, 1,500 and 2,000 dpi. Blue LED Mouse GL9000 makes your life easier because it's tailor-made for right handed users. It just feels great in your hand.

Order Code:
S26381-K438-L100

SpaceMouse™ Pro



Using the SpaceMouse™ Pro 3D mouse to navigate 3D models or environments is as simple as holding them in your hand. A slight movement of the controller cap delivers easy and precise control. SpaceMouse™ Pro is a companion to the traditional mouse and is operated with the free hand. Your traditional mouse hand is free to select, create and edit.

Order Code:
S26381-K459-L100

Keyboard KB900



The KB900 is a very flat keyboard with extra low keys and spill-resistant protection. The elegant design and top-quality construction makes the KB900 the ideal input device for any PC or Notebook user. If you accidentally spill some water or coffee onto the keyboard, this special construction helps the liquid to flow away.

S26381-K560-L4** (**:
Country specific variation)

More information

Fujitsu OPTIMIZATION Services

In addition to the FUJITSU Workstation CELSIUS W520 Long Lifecycle, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about the FUJITSU Workstation CELSIUS W520 Long Lifecycle, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/fts/CELSIUS

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
© 2015 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions
Website: www.fujitsu.com/fts
2016-01-06 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
© 2015 Fujitsu Technology Solutions GmbH