

FUJITSU Image Scanner fi-7140

The essential fi Series scanner with exceptional business performance



shaping tomorrow with you


■ fi-7140 Features

■ Outstanding paper feeding delivers reliable batch scanning regardless of the document condition

The new scanners allow the user to scan a wide variety of paper thicknesses (27 to 413 g/m²), as well as plastic cards with the same feeding mechanism inherited from our high-end models. In addition, Paper Protection constantly checks along the whole document length during scanning and automatically stops paper feeding when error occurs to avoid any damage to the document. All in all these deliver the reliable scanning experience expected from Fujitsu.

● Reliable Skew Reducer even when scanning a mixed size batch

The fi-7140 automatically detect the document size when scanning a mixed size batch. Furthermore, it is equipped with Skew Reducer to detect the alignment of scanned documents and correct paper skews to minimize missing the edge of the scanned image. Users can rest assured that the result will be good even when scanning documents that are not aligned correctly.



■ Compact design for fast scanning right at your desk

The fi-7140 is a compact model that can be placed on the desk, whether for over-the-counter service or for operations in office. It scans at a speed of 40 ppm (A4, color, 200/300 dpi). Simply press the scan button and it will start scanning within a second. Scanning with the fi-7140 will not keep you, or your customers, waiting.



■ Automatically creates the most suitable high quality image data for OCR process

The PaperStream IP scanner driver, which supports TWAIN/ISIS, saves the inconvenience of fine adjusting the settings for the OCR process. It automatically converts the images into exceptionally clean images, accelerating OCR even when scanning wrinkled or soiled documents or documents with a background pattern.

■ Option: Post Imprinter

The optional imprinter unit prints identification markers like dates, alphanumeric codes and symbols on reverse side of the original document. This makes it easier to locate the originals of scanned document when you need to reference them.



Post Imprinter (fi-718PR)

■ Option: Carrier Sheets

Carrier Sheets allow you to scan documents, photos or clippings larger than A4 size. Documents larger than A4 (such as A3 or B4) or photos and clippings that can be damaged easily can be digitized when using the Carrier Sheets.

* Carrier Sheets (5 sheets per set) can be purchased separately. (The Carrier Sheet should be replaced approximately every 500 scans)



A3 Carrier Sheets

■ Options

| Description | Parts number | Comments |
|---------------------------|--------------|---|
| Post Imprinter (fi-718PR) | PA03670-D201 | Assists document management by printing numbers, Roman characters and codes on original documents after they have been scanned. |
| Carrier Sheets | PA03360-0013 | Each package contains 5 carrier sheets. It is recommended that each carrier sheet be replaced after it has been used for 500 scans. |

■ Consumables

| Description | Parts number | Comments |
|-----------------|--------------|--|
| Brake Roller | PA03670-0001 | Lifetime: Every 200,000 sheets or one year. These rollers separate documents as they are being fed into the scanner. |
| Pick Roller | PA03670-0002 | Lifetime: Every 200,000 sheets or one year. These rollers feed documents into the scanner. |
| Print Cartridge | CA00050-0262 | Lifetime: 4,000,000 printed characters fi-718PR print head |

■ Trademarks

- * ABBYY and FineReader are trademarks of ABBYY Software, Ltd. which may be registered in some jurisdictions.
- * ISIS is a registered trademark of EMC Corporation in the United States.
- * Microsoft, Windows, Windows Server, Windows Vista and SharePoint are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.
- * Other company names and product names are the registered trademarks or trademarks of the respective companies.

■ fi-7140 Technical Specifications

| Description | | fi-7140 |
|---------------------------------------|----------------------|---|
| Supported operating systems | | Windows® 8/8.1 (32-bit/64-bit), Windows® 7 (32-bit/64-bit), Windows Vista® (32-bit/64-bit), Windows Server® 2012 R2 (64-bit), Windows Server® 2012 (64-bit), Windows Server® 2008 R2 (64-bit), Windows Server® 2008 (32-bit/64-bit) |
| Scanner type | | Automatic Document Feeder (ADF) |
| Scanning modes | | Simplex / Duplex, Color / Grayscale / Monochrome |
| Image sensor type | | Color CCD (Charge-coupled device) x 2 (front x 1, back x 1) |
| Light source | | White LED Array x 2 (front x 1, back x 1) |
| Multifeed detection | | Ultrasonic multi-feed detection sensor x 1, Paper detection sensor |
| Document size | Maximum | 216 x 355.6 mm (8.5 x 14 in.) |
| | Minimum*1 | 50.8 x 54 mm (2 x 2.13 in.) (Landscape / Portrait) |
| | Long page scanning*2 | 216 x 5,588 mm (8.5 x 220 in.) |
| Paper weight (Thickness)*3 | Paper | 27 to 413 g/m ² (7.2 to 112 lbs) *A8 size: 127 to 209 g/m ² (34 to 56 lb) |
| | Plastic Card | 1.4 mm or less*4 |
| Scanning speed (A4 Portrait)*5 | Color*6 | Simplex: 40 ppm (200/300 dpi), Duplex: 80 ipm (200/300 dpi) |
| | Grayscale*6 | |
| | Monochrome*7 | |
| Paper chute capacity (A4 Landscape)*8 | | 80 sheets (A4: 80 g/m ² or 20 lb) |
| Background colors | | White / Black (Selectable) |
| Optical resolution | | 600 dpi |
| Output resolution*9 | Color (24-bit) | 50 to 600 dpi (adjustable by 1 dpi increments), 1,200 dpi (driver)*10 |
| | Grayscale (8-bit) | |
| | Monochrome (1-bit) | |
| Output format | Color | 24-bit |
| | Grayscale | 8-bit |
| | Monochrome | 1-bit |
| Internal video processing | | 65,536 levels (16-bit) |
| Interface | | USB2.0 |
| Connector shape | | B type |
| Image processing functions | | Multi image output, Automatic color detection, Blank page detection, Dynamic threshold (iDTC), Advanced DTC, SDTC, Error diffusion, Halftone, De-Screen, Emphasis, Color cleanup, Dropout color (None /Red /Green /Blue /Saturation), sRGB output, Hole punch removal, Index tab cropping, Split image, De-Skew, Edge correction, Vertical streaks reduction, Automatic page size detection |
| Power requirements | | AC 100 to 240 V ± 10% |
| Power consumption | | Operating: 36 W or less Sleep mode: 1.8 W or less Auto standby (OFF) mode: 0.35 W or less |
| Operating environment | | Temperature: 5 to 35 °C (41 to 95 °F) Relative humidity: 20 to 80% (Non-condensing) |
| Dimensions: Width x Depth x Height*11 | | 300 x 170 x 163 mm (11.81 x 6.69 x 6.42 in.) |
| Weight | | 4.2 kg (9.26 lb) |
| Included software / drivers | | PaperStream IP (TWAIN/TWAIN x64/ISIS), Software Operation Panel, Error Recovery Guide, PaperStream Capture, ScanSnap Manager for fi Series*12, Scan to Microsoft SharePoint*12, ABBYY FineReader for ScanSnap™*12, Scanner Central Admin Agent |
| Environmental compliance | | ENERGY STAR® and RoHS |
| Included items | | ADF paper chute, AC cable, AC adapter, USB cable, Setup DVD-ROM |

*1 The minimum scanning area only applies to using the ADF.

*2 Capable of scanning documents that exceed Legal sheets in length. Long page scanning supports documents with a length of up to 5,588 mm (220 in.) when the resolution is set to 200 dpi or less.

*3 The paper weight only applies to using the ADF.

*4 Capable of scanning up to 3 cards at a time. (Note: does not support multi-embossed card feedability.)

*5 Actual scanning speeds are affected by data transmission and software processing times.

*6 Indicated speeds are from using JPEG compression.

*7 Indicated speeds are from using TIFF G4 compression.

*8 Maximum capacity varies, depending upon paper weight.

*9 Selectable maximum density may vary depending on the length of scanned document.

*10 Scanning limitations brought about by scanning mode, document size and available memory may occur when scanning at higher resolutions (600 dpi or higher).

*11 Excluding the ADF paper chute and Stacker.

*12 The software can be downloaded from the website designated in the Setup DVD-ROM.

⚠ Safety Precautions

- Be sure to carefully read all safety precautions prior to using this product and use this device as instructed.
- Do not place this device in wet, moist, steamy, dusty or oily areas. Using this product under such conditions may result in electrical shock, fire or damage to this product.
- Be sure to limit the use of this product to listed power ratings.

Visit the fi Series web site for ordering and purchasing information

<http://imagescanner.fujitsu.com>



PFU Limited, a Fujitsu company, has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR® is a registered trademark of the United States.